ROADWAY PAVEMENT STRUCTURAL SECTIONS						
STREET CLASSIFICATION	MINIMUM TRAFFIC INDEX	REFERENCE STANDARD DRAWING NUMBER	AC PAVEMENT TYPE ⑤	MINIMUM AC PAVEMENT SECTION	MINIMUM AC FULL-DEPTH SECTION	MINIMUM PCC PAVEMENT SECTION 4
ALLEY ③	5.5	1111	BASE PAVE: B-PG 64-10	4"AC/6" CAB	7" AC	N/A
LOCAL STREET ③	5.5	1051, 1052		4"AC/6" CAB	7" AC	N/A
LOCAL INDUSTRIAL STREET ③ / COLLECTOR STREET	8	1053, 1054	<u>2" CAP PAVE:</u> ARHM-GG- C-PG 64-16	6"AC/8" CAB	10" AC	N/A
MINOR ARTERIAL/OTHER PRINCIPAL ARTERIAL	10	1055, 1056, 1057		7"AC/8" CAB	11" AC	N/A
OTHER PRINCIPAL ARTERIAL / TRUCK ROUTES	12	1058, 1059, 1060, 1061		8"AC/10" CAB	12" AC	10" PCC/ 6" CAB

NOTES

- 1 PAVEMENT STRUCTURAL SECTION SHALL BE INDICATED ON THE CONSTRUCTION PLANS AND SHALL BE DETERMINED BY A SOIL TEST UTILIZING THE TRAFFIC INDEX PROVIDED BY THE CITY ENGINEER AND A MAXIMUM R-VALUE OF 50. IF THE RECOMMENDED STRUCTURAL SECTION DIFFERS FROM THIS STANDARD DRAWING, THE THICKER SECTION OF THE TWO SHALL BE CONSTRUCTED.
- ② FULL-DEPTH AC SECTION MAY ONLY BE USED FOR TRENCH REPAIRS WITH A MAXIMUM WIDTH OF 12". OTHER APPLICATIONS ARE SUBJECT TO THE APPROVAL OF THE CITY ENGINEER.
- THIS STANDARD DRAWING APPLIES TO BOTH PUBLIC AND PRIVATE STREETS UNLESS OTHERWISE APPROVED BY THE CITY ENGINEER.
- 4 CONCRETE PAVEMENT SHALL MEET CURRENT GREENBOOK STANDARDS AND SPECIFICATIONS.
- (5) ASPHALT CONCRETE (AC) SHALL BE IN ACCORDANCE WITH CURRENT GREENBOOK AND SPECIFICATIONS.

